

USG CEILINGS® KITCHEN LAY-IN PANEL

USG CEILINGS® KITCHEN LAY-IN PANEL

- ClimaPlus[™] 30 year limited system warranty.
- Smooth washable, water repellent, scratch and soil resistant finish
- Meets USDA/FSIS guidelines for use in food-processing areas
- **Insert product representative here>** or 800.874.4968 for technical questions.

Note to specifiers:

This document is not intended to function as a standalone specification. It is intended to assist the specifier in inserting the proper language into the following recommended specification sections:

- 09 51 13 Acoustical Panel Ceilings
- 09 51 23 Acoustical Tile Ceilings

2.3 ACOUSTICAL TILES

A. Acoustical Panel Type:

- 1. Basis of Design: Subject to compliance with project requirements, the design is based on the following: USG Interiors, LLC, "USG Ceilings® Kitchen Lay-In Panel".
- 2. Classification: Provide ceiling panels complying with ASTM E 1264 for type, form and pattern as follows:
 - a. Type: IX, mineral base with scrubbable pigmented or clear finish
 - b. Form: 2, Water Felted
 - c. Pattern: G, Smooth.
- 3. Color: Flat White 050.
- 4. LR: Not less than 0.90.
- 5. NRC: Not less than N/A
- 6. CAC: Not less than 35.
- 7. Edge/Joint Detail: SQ Square.
- 8. Suspension Grid Width: [DX/DXL] [DXLA] [ZXLA] [15/16 inch (24 mm)].
- 9. Panel Thickness: 5/8 inch (15.9 mm).
- 10. Modular Size: [24 by 24 inches (610 by 610 mm)] [24 by 48 inches (610 by 1220 mm)] [As indicated on Drawings] [As indicated in a schedule].
- 11. Recycled Content: Up to [24%].
- 12. ClimaPlus[™] 30 year limited System Warranty. Contains a broad spectrum antimicrobial additive on the face and back of the panel that provides resistance against the growth of mold and mildew. Includes sag resistance performance.

Disclaimer: The USG Product Specifications contained herein are intended for use as product reference material by architects, engineers, other design professionals, contractors, building code officials, or other competent construction industry trade professionals having an interest in the selection, specification and use of products manufactured by the subsidiaries of USG Corporation. The Specifications are intended solely as technical support incident to the sale and use of USG products and not intended to be a substitute for the design review and approval of the licensed design professionals for the project. These materials may be printed and/or transferred electronically solely as needed by the user.