



USG DONN® BRAND AX™ACOUSTICAL SUSPENSION SYSTEM

Product Summary:

- Meets 2014 guidelines for healthcare facilities.
- Noncorrosive aluminum 15/16" exposed grid system with stainless steel clip, ideal for high-humidity or wet-cleaned areas.
- Capable of withstanding cleaning and/or disinfecting chemicals as tested in accordance with ASTM D5402.
- No crevices between suspension system and tile.
- Tested for environmental conditions in accordance with ASTM C635.
- Aluminum components can be used in nonmagnetic environments and meet USDA/FSIS requirements.
- Cross-tee override ends resist twisting and give a professionally finished look.
- Proprietary stainless steel QUICK-RELEASE™ clip.
- Non-fire rated applications only
- Not intended for exterior use.
- <insert product representative here> or 800.874.4968 for technical questions

Note to Specifier:

This document is not intended to function as a standalone specification. It is intended to assist the specifier in inserting the proper language into the following recommended specification sections:

09 51 13 Acoustical Panel Ceilings

09 51 23 Acoustical Tile Ceilings

09 51 33 Acoustical Metal Pan Ceilings

09 54 23 Linear Metal Ceilings

2.5 METAL SUSPENSION SYSTEM FOR ACOUSTICAL CEILING PANEL

- A. Aluminum double-web design; bottom face with; 15/16" (24mm) exposed flange with pre-painted aluminum cap; cross tee holes and hanger wire holes at 6 in oc; integral reversible splices as defined by: ASTM C635, commercial quality pretreated and painted, exposed surfaces prefinished in manufacturer's standard corrosion resistant enamel paint finish. Cross tees; roll-formed aluminum into double-web design with rectangular bulb; 15/16 (24mm) in exposed flange with pre-painted aluminum cap; Stainless Steel clips clenched to the web Main tees and cross tees shall be positively locked, yet shall be removable without the use of tools:
1. Basis of Design: Subject to compliance with project requirements, the design is based on the following: USG Interiors, LLC, "USG DONN® Brand AX™ 15/16" Acoustical Suspension System".
 2. Structural Classification: light duty.
 3. Tee Profile: Standard Face 15/16" (24 mm) wide.
 4. Tee Height: 1 1/2" (38 mm).
 5. Grid Module: [As noted on drawings].
 6. Fire Rating: Class A.
 7. Color: standard flat white 050.
 8. Recycled Content: up to 90%.

B. Accessories.

1. Wall molding, L-shape aluminum: Inside Corner: Field-mitered joints at wall molding. Prefabricated corner cap; formed to 90° angle; hemmed edge; size and finish to match wall molding. Outside Corner: Prefabricated corner cap; formed to 90° angle; hemmed edge; size and finish to match wall molding.
 - a. Angle shape; 7/8 in. thick mounting flange by 7/8 in. thick face flange; hemmed edges; exposed surface pre-finished to match suspension system components. Available Product: M7A.
2. Channel Molding, U-shape aluminum: pre-finished exposed surface to match suspension system components with hemmed edges.
 - a. U mold 1-9/16" x 1/2" x 1" Available product: UA 25.

C. Suspension System Attachment devices.

1. Hanger Wire: Galvanized carbon steel; soft temper; pre-stretched; yield stress load at least three times the design load but not less than 12-gauge.
 - a. Spacing and gauge per IBC, UL and Cisca design.
 - b. Supplied and installed by ceilings subcontractor.

Disclaimer: The USG Product Specifications contained herein are intended for use as product reference material by architects, engineers, other design professionals, contractors, building code officials, or other competent construction industry trade professionals having an interest in the selection, specification and use of products manufactured by the subsidiaries of USG Corporation. The Specifications are intended solely as technical support incident to the sale and use of USG products and not intended to be a substitute for the design review and approval of the licensed design professionals for the project. These materials may be printed and/or transferred electronically solely as needed by the user. Because electronic text files can be modified by other parties, without notice or indication of such modifications, modification of USG Product Guide Specifications and Drawings is the sole responsibility of the Design Professional.